

Full Tank

HYDRAULIC SWING GATE OPERATOR FOR CONDOMINIUM /INDUSTRIAL USE FOR LEAF LENGTHS UP TO 7M



•

- Oil lubrication of all mechanical components
- · Noiseless and hydraulic reliability
- Anti crushing guaranteed through by-pass valves for max. thrust adjustment
- 270mm or 390mm stroke
- Available versions with hydraulic slowdown in closing (on request also adjustable)
- Versions (AC) with lock in opening and closing, (SC) only in closing, (SA) only in opening, (SB) without lock.
- 20mm rod diameter
- Standard, oscillating aluminium fork back fixing
- Hydraulic distributer out of strong aluminium





Release with lock in case of eletric power cut

Round joint for stroke adjustment

R

On request versions with hydraulic slowdown for a smooth approach of the leaves in closing

CODE	NAME	MAX LEAF WEIGHT (KG)	MAX LEAF LENGTH (M)	MAX OPENING DEGREE	MAX CYCLES/ HOUR	PCS FOR PALLETS
10601005	FULL TANK 270 AC	1000	1,8	120°	70	40
10631005	FULL TANK 270 SC	1000	1,8	120°	70	40
10611005	FULL TANK 270 SA	1000	7,0	120°	70	40
10621010	FULL TANK 270 SB	1000	7,0	120°	70	40
10601060	FULL TANK 270 DOUBLE AC	1000	1,8	120°	70	12
10621050	FULL TANK 270 DOUBLE SB	1000	7,0	120°	70	12
10701010	FULL TANK 390 AC	1000	2,2	120°	70	27
10731005	FULL TANK 390 SC	1000	2,2	120°	70	27
10711005	FULL TANK 390 SA	1000	7,0	120°	70	27
10721005	FULL TANK 390 SB	1000	7,0	120°	70	27

N.B: DOUBLE version includes GATE 2 ROLL control unit + 433 MHz receiver

ACCESSORIES



12715105

PS270 Kit mechanical PS390 stop for FT 279 stop for

PS390 Kit mechanical stop for FT 390

12715110

23105335

management





23105345(*)

SAFETYGATE linear encoder kit for 220V swing operator for control units with encoder management (side wall)

🤄 Sea


SAFETYGATE encoder kit for 220V swing operator for control units with encoder 65000045

12715070

BRA Adjustable back bracket to screw n.2 pcs

OILH green oil for hydraulic motors (5 liters)

(*)in case of opening with lateral wall



FULLTANK 390

