



Variants of the drive cross section:

- Header profile 2101/2201/2202
- Header profile 2101/2201/2202 H100 (according to drawing)

The door leaves must be made from material which do not bear any potential risk of injury in any case of breakage (for example single sheet toughened safety glass, compound safety glass etc.). Transparent door leaves must be clearly labelled to be recognised as such.

* Safety margin according to national regulation

Anodize/color: layer thickness: _____ Additional info:
RAL: _____

Object: _____

Customer: _____

Order-Nr.: _____ Date: _____ Release signatur: _____

b Executed on site

k1 Distance, type and number of fixing screws are to be defined due to the building's material structure and the necessary stability

LB1=1.5W+76+S	GB1=FB1-44
W=(LB1-S-76)/1.5	GB2=FB2-44
LVmin=LB1-12	GB3=FB3-44
LKmin=LVmin-2	FH1=FH2=LH+17.5
FB1=W/2+33	GH1=FH1-95
FB2=W/2+33	GH2=FH2-95
FB3=W/2+S+21	GH3=FH3-95

Scale	Drawn	22.11.19	MURO
%	ok to print		
Operator type: Profilsystem Execution		Document number: T3_390_753	
		TORMAX a Division of LANDERT Group AG CH-8180 Bülach-Zürich	