



America

CERTIFICATE

No. U10 015347 0526 Rev. 00

Holder of Certificate: **TORMAX**
A Division of LANDERT Group AG
Unterweg 14
8180 Bülach
SWITZERLAND

Certification Mark:



Product: **Automatic door drives**

Tested according to: UL 325:2017/R:2020-02
CAN/UL 325:2017

This product was voluntarily tested to the relevant safety requirements referenced on this certificate. It can be marked with the certification mark above. The mark must not be altered in any way. The certificate holder shall not transfer this certificate to third parties. This product certification system operated by TÜV SÜD America Inc. most closely resembles system 3 as defined in ISO/IEC 17067. Certification is based on the TÜV SÜD "Testing and Certification Regulations". For Canadian standards TÜV SÜD America Inc. is accredited by the Standards Council of Canada to ISO/IEC 17065.

Test report no.: 713274804

Date, 2022-12-23

(Benedikt Pulver)



America

CERTIFICATE

No. U10 015347 0526 Rev. 00

Model(s): TORMAX 1102 Swing Door Drive / TTX 1102
TORMAX 1201 Swing Door Drive

Brand Name(s): TORMAX

Parameters:

| Type: | 1102 / TTX 1102 | 1102 / TTX 1102 | 1201 | 1201 |
|---|--------------------------------------|--------------------|---------------------|-------|
| Rated voltage: | 115 V | 230 V | 230 V | 115 V |
| Rated frequency: | 60 Hz | 50 Hz ... 60Hz | | 60 Hz |
| Rated power input max.: | 210 W | | 235 W | |
| Rated current max.: | 2.1 A | 1.05 A | 1.15 A | 2.3 A |
| Protection class: | I | | | |
| Degree of protection: | IP20 | | | |
| Number of door leaves: | 1 | | | |
| Weight of door leaf max.: | 125 kg | | 250 kg | |
| Width of door leaf max.: | 1.2 m | | 1.4 m | |
| Moment of inertia max.: | 35 kgm ² | | 65 kgm ² | |
| Temperature range: | -20 °C ... +50°C | | | |
| Performance Level: | c | | | |
| Category: | 2 | | | |
| Firmware version: | V04.00 and V04.31 | | | |
| Classification: | | | | |
| 1 kind of drive | 1: Swing door drive | | | |
| 2 durability | 3: 1.000.000 cycles | | | |
| 3 leaf construction | *) | | | |
| 4 fire protections door | *) | | | |
| 5 safety devices | 1: Force limitation | | | |
| | 2: External safety devices, optional | | | |
| | 3: Low energy, optional | | | |
| 6 special requirements | 0: no special requirements | | | |
| 7 safety at the door system | *) | | | |
| 8 ambient temperature | 4: manufacturers data -20°C - +50°C | | | |
| *) The system installer has to determine the numbers not stated and has to ensure that by that selection the normative requirements are fulfilled. Fire door set properties were not part of this test. | | | | |



America

CERTIFICATE

No. U10 015347 0526 Rev. 00

Conditions of Acceptability:

- When installing the equipment, all requirements of the standards and the manufacturer's specifications must be met.
- The product is for building in with doors and external entrapment protections at final installation site.
- External entrapment is not supplied by the manufacturer and shall be connected, installed, setup with the controller at the installation site for correct operation prior to use.
- The maximum investigated branch circuit rating is 20 A.
- The product was investigated for indoor use only.
- The product was investigated for Pollution Degree 2.
- Upon installation the clearance and creepage distance between the hazardous voltage parts and accessible parts shall meet the standards' requirements.
- Evaluated as Protection Class I (earthed equipment). Proper and reliable ground bonding to the main protective earthing terminal is required at final installation.
- This operator is equipped for permanent wiring.
- The operators are to be installed only by trained service personal according to manufacturer installation instructions.
- All installation and setup requirements from the manufacturer shall be followed at the final installation location. Failure to follow these instructions could result in severe injury or death to persons.
- All external labelling, warning signs and placards must be installed where visible in the area of door per manufactures instructions.